

USE & CARE GUIDELINES FOR PAPERSTONE®



CDUK would recommend using the following products to clean, maintain and care for your PaperStone® worksurfaces.

Osmo® Liquid Wax Cleaner Spray 3029 for intensive cleaning and refreshing

- Cleans and regenerates the PaperStone® at the same time
- Removes tough stains
- Maintains protected surfaces without wear of treatment
- Easy to use for occasional use
- Provides PaperStone® with natural hard waxes
- Ideal for domestic and commercial use

Clear liquid wax cleaner should be used occasionally to refresh and rejuvenate your PaperStone® worksurfaces or remove tough, stubborn stains. By doing this the surface is provided with the natural, safe hard waxes (carnauba and candelilla waxes) to remain hard-wearing without forming a film.

Osmo® Liquid Wax Cleaner 3029 contains natural plant waxes (carnauba wax, candelilla wax); paraffin, aliphatic hydrocarbons (> 30%). Detailed declaration of ingredients available at www.osmouk.com.

For removing stains and for intensive maintenance, use Osmo® Liquid Wax Cleaner with a microfibre cloth or non-abrasive sponge. Use approx. 2 teaspoons per m². The surface must be dust-free and dry. Rub away especially tough stains and all of the surrounding surface areas with Osmo® Liquid Wax Cleaner. Leave approx. 30-40 minutes to dry thoroughly. Ventilate well while drying.

Osmo® Spray Cleaner 8026 for everyday cleaning and care

- Highly effective cleaning
- Maintains protected surfaces without wear of treatment
- Easy to use, simply spray and wipe clean
- Moisturises the surface to maintain freshness
- Suitable for domestic and commercial use

Osmo® Spray Cleaner is a ready-to-use spray solution for daily cleaning and maintenance – especially developed for surfaces oiled using Osmo® TopOil. It contains soaps based on natural oils. Osmo® Spray Cleaner cleans the surface without removing oils and waxes. Spray Cleaner does not dry the PaperStone® surface out. It is especially mild on skin, free of dyes and fragrances, biodegradable, free of solvents and emissions.

Turn the spray nozzle to open and spray Osmo® Spray Cleaner directly onto the surface. Rub the entire surface with a microfibre cloth. Leave to dry for 5-10 minutes.



CDUK, Baker House, Thistle Way, Gildersome Spur, Leeds LS27 7JZ

tel 0113 201 2240 email info@cdukLtd.co.uk cdukLtd.co.uk

CDUK is a trading division of CD (UK) Ltd.